



ComboFoam® is an Acoustic Underlayment & Moisture Barrier for use in residential and commercial flooring applications. As part of our *Value* Collection, ComboFoam is a fine choice for most Laminate, Engineered and Solid hardwood flooring installations. ComboFoam can be used in Floating and Nail down installations.

## TYPICAL PHYSICAL PROPERTIES SHEET

### GENERAL PROPERTIES

---

Item Name	ComboFoam®
Construction	Closed cell polyethylene
Overlap Options	Available with UltraSeal Self Sealing Lip & Tape
Thickness	2 mm
Coverage Area	100 sf
Standard Roll Size	46" wide x 26 lf
Product Grade	Value

### PERFORMANCE

---

Impact Isolation Class ( IIC )	up to (61) dB per ASTM E 492 / ASTM E 989
Sound Transmission Class ( STC )	up to (54) dB per ASTM E 90
Moisture Vapor Transmission Rate	up to (2.0) lbs / 1000 ft <sup>2</sup> / 24 hr. per ASTM E 96
Compressive Strength @ 25%	≥ 3.5 psi per ASTM D 3575
Warranty Period	10 Years
Mold and Mildew Resistant	Yes
R Value	Adds R value to chilly floors
Volatile Organic Compounds (VOCs)	100% LDPE product - resilient, nonreactive
Recyclable	Yes

### PACKAGING

---

Rolls / Carton	18
Cartons / Skid	8
Skids / TL	26
Rolls / TL	3,744
SF / Carton	1,800 sf
SF / Skid	14,400 sf
SF / TL	374,400 sf

The data represented on this Typical Property Sheet reflects averages derived from product sample testing on limited production runs, and may be changed without notice. Actual product properties are subject to normal manufacturing and testing tolerances. This is especially true for conventional measurements of weight, thickness, and density. This Typical Property Sheet is not intended to represent, replace, or be used as a proxy for a specific product sales specification. Please refer to our website at [www.floormuffler.com](http://www.floormuffler.com) for the most up to date product information, data, and installation instructions.



Diversified Industries  
121 High Hill Road  
Swedesboro, NJ 08085  
is a proud member of the  
**MADE IN NEW JERSEY**  
Program

Let's Get Social



Value  
GRADE