floorMuffler®

it's what's underneath that counts®

High Performance Acoustic Underlayment & Moisture Barrier



FloorMuffler® is a high performance Acoustic Underlayment & Moisture Barrier for use in residential and commercial flooring applications. As part of our Premium Collection, FloorMuffler is the ideal choice for most Laminate, Engineered and Solid hardwood flooring installations. FloorMuffler can be used in Floating, Nail down, and Double glue down installations. Available both with and without UltraSeal self-sealing lip & tape system.

TYPICAL PHYSICAL PROPERTIES SHEET

GENERAL PROPERTIES

FloorMuffler® / FloorMuffler® UltraSeal Item Name

Construction Closed cell, polypropylene foam

Overlap Options Available both with & w/o UltraSeal Self Sealing Lip & Tape

Thickness 2 mm

100 sf / 600 sf Coverage Area

Standard Roll Size 39" wide x 30.75 lf / 72" wide x 100 lf

Product Grade Premium

PERFORMANCE

Impact Isolation Class (IIC) up to (74) dB per ASTM E 492 / ASTM E 989

Delta Impact Isolation Class (ΔIIC) up to (25) dB per ASTM E 2179 Sound Transmission Class (STC) up to (73) dB per ASTM E 90

(.3) lbs / 1000 ft² / 24 hr. per ASTM E 96 Moisture Vapor Transmission Rate

Compressive Strength @ 25% ≥ 11 psi per ASTM D 3575 Flammability Class A per ASTM E 84

Warranty Period Limited Lifetime

Mold and Mildew Resistant Yes

3 ft²-F-hr/BTU-in R Value

Volatile Organic Compunds (VOCs) Surpasses California Section 03150

Recyclable Yes

PACKAGING

Rolls / Carton (12) 100 sf / (8) 600 sf Cartons / Skid (10) 100 sf / (2) 600 sf

Skids / TL 26

Rolls / TL (3,120) 100 sf / (416) 600 sf SF / Carton (1,200) 100 sf / (4,800) 600 sf SF / Skid (12,000) 100 sf / (9,600) 600 sf SF/TL (312,000) 100 sf / (249,600) 600 sf

The data represented on this Typical Property Sheet reflects averages derived from product sample testing on limited production runs, and may be changed without notice. Actual product properties are subject to normal manufacturing and testing tolerances. This is especially true for conventional measurements of weight, thickness, and density. This Typical Property Sheet is not intended to represent, replace, or be used as a proxy for a specific product sales specification. Please refer to our website at www.floormuffler.com for the most up to date product information, data, and installation instructions.

et's Get Social



Diversified Industries 121 High Hill Road Swedesboro, NJ 08085 is a proud member of the MADE IN NEW JERSEY Program









