



# PALL-X KITT

Water-based joint filler compound for wood floors

## Description

PALLMANN® Pall-X Kitt is a water-based joint filler compound that is mixed with sanding dust and used for joint and trowel filling of wood floors. It is suitable for strip, plank and parquet flooring of all species where color-matching is important and where filler stability and adhesion are vital. Pall-X Kitt's viscous, paste-like mixture is rated for radiant heat floor systems.

## Features

- Uses sanding dust from floor to be filled
- Ready to use, fast drying formula
- No-clog formula
- High viscosity

## Benefits

- Perfect color matching
- Saves time
- Will not load or waste abrasives
- Holds well in gaps

## Technical Data

Packaging:	1 U.S. plastic gallon
Color:	Milky yellow when wet, color-matched to species when dry
VOC Content:	VOC does not exceed 100 grams per liter
Stability:	Minimum 12 months
Mixing Ratio:	Blend to a paste consistency that can be trowel applied
Working Temp.:	65-75°F (18-25°C) for optimum performance
Coverage Rate:	Approx. 400 sq. ft. per gallon, depending on floor condition
Ready for Sanding:	15-25 minutes
Storage:	Store between 50-70°F (10-20°C). Keep from freezing.

## Directions for Use

1. Shake Product Well.
2. Pour the Pall-X Kitt into a 'crater' of sanding dust on the floor to be filled. Using a stainless steel trowel (Item #12506), blend the liquid with the dust to achieve a trowelable paste consistency.
3. Trowel apply to the floor, filling all joints and gaps. **NOTE:** From time to time it will be necessary to add more Kitt liquid to the mix on the floor to maintain a paste-like consistency. Pall-X Kitt may also be mixed with sanding dust in a bucket prior to trowel application.

## Important Notes

- The filling application should be made before the final cut with the belt or drum sander.
- The floor can normally be sanded 15 to 30 minutes after filling. High humidity and/or low temperature conditions may extend the dry time while increased ventilation and airflow may reduce dry time.
- It is recommended to make your final cut with a belt or drum sander to remove any residual filler. Additional sanding with screens or discs at your discretion.

## Clean Up

Tools and applicators should be cleaned with water.

## Storage

Minimum 24 months in original packaging when stored under normal conditions (50-70°F/10-20°C). Tightly reseal opened containers. Keep from freezing.

## Disposal

Dispose of empty containers according to local, state and federal regulations.

## Precautions

CAUTION: Keep out of reach of children. Keep container closed during storage. Avoid contact with eyes and skin. Avoid breathing vapors. Use only in well-ventilated areas. Use of protective gloves (rubber) and safety glasses is recommended. Non-flammable.

FIRST AID: In case of skin contact, wash thoroughly with soap and water. For eye contact, flush immediately with large amounts of water for at least 15 minutes and obtain medical treatment. If swallowed, obtain medical treatment immediately.



MIXES WITH  
SANDING  
DUST

A Brand Of

**UFLOOR**  
SYSTEMS

UFLOOR Systems Inc.  
14509 E. 33rd Place, Unit G | Aurora, CO 80011  
Phone: 720.374.4810 | Fax: 720.374.2113  
info@pallmann.us | pallmann.us



**PALLMANN**

wood floors. protected

07/31/15